

BM5263E



DIGITAL SUBLIMATION TEXTILE PRINTER
OPEN YOUR COLORFUL WORLD
TOP SPEED 120m²/h

TECHNICAL PARAMETERS

PRINTHEAD	TYPE: EP54720 PRINTHEAD QUANTITY: 3 PCS RESOLUTION: 3200DPI HEAD CLEAN: PUMP-CLEAN, AUTO-FLASH, ETC.
PRINTING SPEED	3PASS 90m ² /h 4PASS 75m ² /h 6PASS 50m ² /h <small>*Based on fabric of 160gsm and 160cm width</small>
INK	TYPE: SUBLIMATION INK COLOR: C M Y K Ink Supply Method: Siphon Positive Pressure Ink Supply
MEDIA TRANSFER	AUTO TENSION TAKING-UP MEDIA DEVICE
SYSTEM CONFIGURATION	OPERATION SYSTEM: WIN7 64BIT WIN 10(ULTIMATE/PROFESSIONAL) HARD DISK: NTFS, MIN SPACE IN SYSTEM DISK C: 100G, HARD DISK: WG500G GPU: ATI DISCRETE GPU MEMORY: 4G, CPU: INTEL I5/I7 DATA TRANSMISSION PORT: G-ETHERNET
TRANSMISSION INTERFACE	Gigabit LAN
DRYING METHOD	EXTRA INDEPENDENT DRYER
WORK ENVIRONMENT	TEMP.: 20°C-35°C HUMIDITY: 35%-65%
MOISTURE MODE	AUTO-CAPPING PUMP MOISTURE
PRINTING WIDTH	2600mm
RIP SOFTWARE	MainTop / Photoprint / ONYX / Neostampa
IMAGE FORMAT	JPG, TIF, EPS, PDF,
MACHINE DIMENSION	3790*880*1640mm Paking Size: 3940*1185*1805mm
POWER REQUEST	210-230VAC FREQUENCY: 50/60 HZ RC: 16A
POWER PARAMETER	PRINTER: 1200W DRYER: 3600W
Optional	Ink Level Alarm System Auto Media Take-up Unit with Inflatable Roller

Adopt integrated head moisture mode.

Giga-bit Ethernet data transmission port, which is more stable on printing output.

Head position is staggered on carriage plate, which is easier for calibration and adjustment.

Imported spare parts: THK mute guide, Japanese NSK bearing, Germany IGUS ink chain, Leadshine integrated motor.

3 Epson 3200 printhead, 3pass speed can reach up to 90m²/h

Auto taking-up device with tension sensor bar, auto-media sensor and head protection unit.